

# IES-0204FT

## 4-Port 10/100TX + 2-Port 100FX Industrial Switch

- Wide-range redundant power with polarity reverse protection
- Compact size with DIN rail and wall mount design
- Wide operating temperature range from -40°C to 75°C (-E model)
- Provides 3K VDC EFT & 6K VDC ESD protections



### OVERVIEW

The Lantech IES-0204FT is a 4-port 10/100TX + 2-port 100FX Industrial Switch for plug-and-play installation. It can auto detect power inputs and supports wide input range from 9V to 56VDC. To increase reliability, the IES-0204FT provides redundant power design with polarity reverse protection as well as EFT and ESD protections.

The Lantech IES-0204FT is designed to meet the demands of industrial environments, comes packaged in a robust IP-30 housing and has been tested extensively to meet Industrial EMI and EMC standards. Rigorous mechanical testing has also been undertaken with free fall, shock, and vibration stability test,


which ensure long term reliability in critical industrial environments. The -E model can be used in extreme environments with an operating temperature range from -40°C to 75°C.

Featured with relay contact to alarm system, the IES-0204FT can immediately notify of power failure event. The Lantech IES-0204FT is compact in size and easy to be installed with DIN rail and wall mount kit. It is the best choice both in inflammable or normal industrial environment such as automation, transportation, heavy Industrial factory, mining, oil & gas, chemical, and processing automation area.

### FEATURES & BENEFITS

- RJ-45 port support Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- Back-plane (Switching Fabric): 1.2Gbps
- 2K MAC address table
- Supports Wide Operating Temperature (-40°C~75°C)
- Provides EFT protection 3000 VDC for power line
- Supports 6000 VDC Ethernet ESD protection
- IP-30 Protection with DIN Rail and Wall Mount Design
- Power Supply
  - Wide-range Redundant Power Design
  - Power Polarity Reverse Protect
  - Overload Current Re-settable Fuse Present
- Provides broadcast storm protection

### DIMENSIONS (unit=mm)



## SPECIFICATION

Hardware Specification		Overload current protection	Present
IEEE Standards	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX and 100Base-FX Fast Ethernet IEEE802.3x Flow Control and Back Pressure	Power Supply	24 VDC (9-56VDC), 18 VAC( 12-36 VAC), Redundant power with polarity reverse protect function and removable terminal block
Switch Architecture	Back-plane (Switching Fabric): 1.2Gbps Packet throughput ability (Full-Duplex): 1.488Mpps @64bytes	Power Consumption	6.41 Watts
Transfer Rate	14,880pps for Ethernet port 148,800pps for Fast Ethernet port	Operating Humidity	5% ~ 95% (Non-condensing)
Mac Address	2K MAC address table	Operating Temperature	-20°C~60°C / -4°F~140°F (Standard model) -40°C~75°C / -40°F~167°F (E model)
Connectors	10/100TX: 4 x RJ-45 with auto MDI/MDI-X function 100M fiber: 2 x SC type connector for Single-mode or Multi-mode type fiber cable [Multi-Mode] power budget : Min: 9dB , MAX: 19dB. [Single-Mode] power budget : Min: 19dB , MAX: 26dB.	Storage Temperature	-40°C~85°C / -40°F~185°F
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)	Case Dimension	Metal case. IP-30, 30mm (W) x 95mm (D) x 140mm (H)
Optical Cable	Multi-mode: 50/125um~62.5/125um Single-mode: 9/125um Available distance: 2km (Multi-mode)/30km (Single-mode) Wavelength: 1310nm (Multi-mode/Single-mode)	Weight	810 g
Protocol	CSMA/CD	Installation	DIN Rail and Wall Mount Design
LED	Per port: Link/Activity (Green), Full duplex/Collision (Yellow) Per unit: Power 1 (Green), Power 2 (Green), Fault(Red)	EMI & EMS	FCC Class A, CE EN61000-4-2 (ESD), CE EN61000-4-3 (RS), CE EN-61000-4-4 (EFT), CE EN61000-4-5 (Surge), CE EN61000-4-6 (CS), CE EN61000-4-8, CE EN61000-4-11, CE EN61000-4-12, CE EN61000-6-2, CE EN61000-6-4
Reserve polarity protection	Present	Safety	CE/EN60950-1
		Stability Testing	IEC60068-2-32 (Free fall) IEC60068-2-27 (Shock) IEC60068-2-6 (Vibration)
		MTBF	347014 hrs
		Warranty	5 years

## ORDERING INFORMATION

- **IES-0204FT (SC/MM).....P/N: 8350-340**  
4 10/100TX + 2 100FX (SC, MM 2km) Industrial Switch, Standard Operating Temperature (-20°C~60°C)
- **IES-0204FT (SC/SM).....P/N: 8350-341**  
4 10/100TX + 2 100FX (SC, SM 30km) Industrial Switch, Standard Operating Temperature (-20°C~60°C)
- **IES-0204FT-E (SC/MM).....P/N: 8350-345**  
4 10/100TX + 2 100FX (SC, MM 2km) Industrial Switch, Wide Operating Temperature (-40°C~75°C)
- **IES-0204FT-E (SC/SM).....P/N: 8350-346**  
4 10/100TX + 2 100FX (SC, SM 30km) Industrial Switch, Wide Operating Temperature (-40°C~75°C)

## OPTIONAL ACCESSORIES

### DIN Rail Power

- **AD1048-24FS** 24VDC, 2A, Wide AC Input, Convection Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C
- **AD1024-24F** 24VDC, 1A, Wide AC Input, Convection Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C
- **AD1240-48S** 48VDC, 5A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C
- **AD1120-48F** 48VDC, 2.5A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C

Lantech Communications Europe GmbH

[www.lantechcom.eu](http://www.lantechcom.eu) / [www.lantechcom.tw](http://www.lantechcom.tw)  
info@lantechcom.eu

© 2009 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
Lantech may make changes to specification and product descriptions at anytime, without notice.